

MATERIAL SAFETY DATA SHEET

Into Great Brands, Inc.
1010 Taylor Station Rd. Suite A
Gahanna, OH 43230
(888) 771-5656
(800) 424-9300 - Chemtrec

*May be used to comply with OSHA's
Hazard Communication Standard
29CFR 1910.1200. Standard
must be consulted for specific
requirements.*

SECTION I

IDENTIFICATION

Trade Name: *(Aerosol)* Dura Lube Advanced All Purpose Lubricant/Protectant
Product Code: HLSL052C-A
Chemical Class: Petroleum Distillate/Oil Mixture
U.S. D.O.T. Shipping Name: Non Regulated
U.S. D.O.T. Primary Hazard Class: Aerosols,
U.S. D.O.T. Secondary Hazard Class: Combustible Liquid N.O.S.
Identification Number: UN1950
Packing Group: Not Applicable
HMIS: Health, 1 Fire, 2 Reactivity, 1

SECTION II

HAZARDOUS INGREDIENTS--IDENTITY INFORMATION

<u>Hazardous Components</u>	<u>CAS #</u>	<u>WT%</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Aliphatic naphtha	64742-47-8	50	500 ppm	100 ppm
Petroleum Oils	64742-65-0	25	NA	NA

Other components, if any, are considered to be non-hazardous as per OSHA 29 CFR 1910.1200.

SECTION III

PHYSICAL & CHEMICAL CHARACTERISTICS

Flash Point: 175°F ASTM D-56 Tag Closed Cup(as applied)
Specific Gravity (H₂O=1): 0.97 @ 25°C
Vapor Density (Air=1): Greater
Evaporation Rate (BA=1): Slower
% Solids: Negligible
Weight (lb./gal.): 8.11
Solubility in Water: Negligible
Viscosity @25°C: 25-45 cps
Appearance & Odor: Amber liquid, slight organic solvent odor
Physical State: Pressurized aerosol container
Operating Temperatures: Low -80°F / Max Sustained 350°F / Max Intermittent 400°F
VOC: 29.34 %

SECTION IV

FIRE & EXPLOSION HAZARD DATA

Extinguishing Media: Carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Use Self Contained Breathing Apparatus.
Unusual Fire & Explosion Hazards: Contents under pressure. Do not use near sparks, or open flames. Do not puncture or incinerate. Exposure to temperatures above 120°F may cause containers to burst.

SECTION V

REACTIVITY DATA

Stability: Stable.
Conditions to Avoid: Contact with open flame.
Hazardous Decomposition Products: Carbon Monoxide and unidentified organic compounds may be formed during combustion.
Hazardous Polymerization: Will not occur.

SECTION VI

HEALTH HAZARD DATA

SIGNS AND SYMPTOMS OF EXPOSURE:
Eyes: Irritation, redness.
Dermal: Dryness, irritation, redness.
Inhalation: Vapors may irritate nose, throat, respiratory tract.
Ingestion: Nausea, vomiting, dizziness, headache, blurred vision.

EMERGENCY AND FIRST AID PROCEDURES:

Eyes:	Flush with large amounts of water for 15 minutes.
Dermal:	Wash with soap and water.
Inhalation:	Remove victim to fresh air.
Ingestion:	Do Not induce vomiting. Get medical attention.
Acute Health Hazards:	Mild irritation of skin and eyes.
Chronic Health Hazards:	None expected at the industrial level.

SECTION VII

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Dike or pill area. Remove all sources of ignition. Ventilate area if necessary. Absorb free liquid with earth, sand, clay, or absorbent pads and place in non-leak containers for disposal. Flush area for trace residue and dispose of as below.

WASTE DISPOSAL METHOD:

In accordance with Local, State and Federal Laws. The active ingredients in Dura-Lube are considered non hazardous by the U.S. E.P.A. and O.S.H.A.. Since this product contains petroleum oils, it should be disposed of as used oil. It has been tested and determined to be acceptable for recycling and or energy recovery. If this product has been altered with any hazardous substance, it should be treated as such.

SECTION VIII

SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Normally not needed in a well ventilated area.
Ventilation:	Mechanical to maintain good air flow.
Protective Gloves:	Rubber.
Eye Protection:	Goggles or safety glasses.
Other:	As needed to minimize exposure.
Hygienic Practices:	Always wash face and hands after contact.

SECTION IX

NOTES

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in the use of this material.

Revision date: January 24, 2005